

# Grease separator EasyClean free NS 2, Standard, Inspection window



### **Article information**

Item no.: 93002.21 GTIN: 4026092063279 Discount group: 03

## **Advantages**

- Direction of flow can be changed thanks to selfsealing interchangeable hubs
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

manual with suction hose

Standard

## **Description**

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work.

Manual disposal is carried out with the tank open.

20 year polyethylene warranty.

eı	ers	ersio	ersion

Type of disposal:

Disposal variant:

•		
Refill inlet in accordance with DIN 1988:	no	
Nominal size (NS):	2	
Inspection window:	yes	
Shredder-Mix-System:	no	
SonicControl:	no	
Load-bearing capacity (DIN 19901):	F3	
Delivery state:	Installation-ready (connection parts must be connected on site)	

General characteristics:

Material: PE



#### **Dimensions:**

Set-up area, length:

Set-up area, width:

Set-up area, height:

Required access area, length:

Required access area, width:

Required access area, height:

1,434 mm

Required access area, height:

1,434 mm

#### Tank:

Inlet nominal size (DN):

Inlet nominal size (OD):

Outlet nominal size (DN):

Outlet nominal size (OD):

Outlet nominal size (OD):

Distance pipe bottom inlet to tank bottom:

Distance pipe bottom outlet to tank bottom:

985 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

#### Coverage features:

Type of cover:

Cover material:

Colour of cover:

Tightness:

Cover

Polymer

violet

odour-tight

Locking: Quick-release closure

#### Wastewater contents:

Separator contents: 400 l
Total volume: 600 l
Contents of sludge trap: 200 l
Storage quantity of grease: 100 l

#### Control:

Control unit: no