

Grease separator EasyClean free NS 3, Standard



Article information

Item no.: 93003.01 GTIN: 4026092060889 Discount group: 03

Advantages

- Direction of flow can be changed thanks to selfsealing interchangeable hubs
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

manual with suction hose

Standard

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work.

Manual disposal is carried out with the tank open.

20 year polyethylene warranty.

Version:

Type of disposal:

Disposal variants

General characteristics:

| Biopodat variant. | Otaridard |
|---|---|
| Refill inlet in accordance with DIN 1988: | no |
| Nominal size (NS): | 3 |
| Inspection window: | no |
| Shredder-Mix-System: | no |
| SonicControl: | no |
| Load-bearing capacity (DIN 19901): | F3 |
| Delivery state: | Installation-ready (connection parts must be connected on site) |
| | |

Material:

PΕ



Dimensions:

Set-up area, length:

Set-up area, width:

Set-up area, height:

Required access area, length:

Required access area, width:

Required access area, height:

1,434 mm

Required access area, height:

1,434 mm

Tank:

Inlet nominal size (DN):

Inlet nominal size (OD):

Outlet nominal size (DN):

Outlet nominal size (OD):

Distance pipe bottom inlet to tank bottom:

Distance pipe bottom outlet to tank bottom:

985 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

Coverage features:

Type of cover:

Cover material:

Colour of cover:

Tightness:

Cover

Polymer

violet

odour-tight

Locking: Quick-release closure

Wastewater contents:

Separator contents: 300 l
Total volume: 600 l
Contents of sludge trap: 300 l
Storage quantity of grease: 120 l

Control:

Control unit: no