

Grease separator EasyClean free NS 7, Auto Mix



Article information

Item no.: 93007.01/DSP

GTIN: 4026092060827

Discount group: 03

Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs
- Low-maintenance operation
- Customisation possible through control unit

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work.

The innovative Shredder-Mix-System with integrated macerating system is responsible for homogenising and circulating the tank contents. Cleaning is carried out by an exterior pump which can be disconnected from the tank by a shut-off valve. A direct disposal pipe socket is available for odour-neutral manual disposal.

The fully automatic program run is controlled by a user-friendly control unit with multi-line display that can be integrated into the building management system through a potential-free contact. Cleaning and disposal can be started remotely using the remote control, which is available as an option.

Thanks to the customisable cleaning program with fast-selection function, cleaning can be adapted to the local circumstances as required. After disposal, a maximum of 3 litres residual sludge volume is left in the tank. Observance of the Drinking Water Hygiene Directive can be guaranteed through the fully automatic rinsing of the drinking water pipes.

20 year polyethylene warranty.

Installation situation:

free-standing set-up

Version:

Shut-off valve:

yes

Type of disposal:

automatic cleaning system

Disposal system:	Disposal connection
Disposal variant:	Auto Mix
Refill inlet in accordance with DIN 1988:	yes
Nominal size (NS):	7
Inspection window:	yes
Shredder-Mix-System:	yes
SonicControl:	no
Water supply:	2 solenoid valves 1"
Load-bearing capacity (DIN 19901):	F3
Delivery state:	Installation-ready (electrical components, connection parts must be connected on site)
Scope of delivery:	Storz-B coupling R 2 1/2" for disposal vehicle connection

General characteristics:

Material:	PE
Standard:	EN 1825

Dimensions:

Set-up area, length:	2,147 mm
Set-up area, width:	1,108 mm
Set-up area, height:	1,892 mm
Required access area, length:	1,910 mm
Required access area, width:	940 mm
Required access area, height:	1,678 mm

Tank:

Inlet nominal size (DN):	150
Inlet nominal size (OD):	160 mm
Outlet nominal size (DN):	150
Outlet nominal size (OD):	160 mm
Distance pipe bottom inlet to tank bottom:	1,255 mm
Distance pipe bottom outlet to tank bottom:	1,185 mm
Pressure pipe connection (DN):	65 mm
Pressure pipe connection (OD):	75 mm
Nominal pressure (PN):	10
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

Coverage features:

Type of cover:	Cover
Cover material:	Polymer

Colour of cover:	violet
Tightness:	odour-tight
Locking:	Quick-release closure

Wastewater contents:

Separator contents:	650 l
Total volume:	1,350 l
Contents of sludge trap:	700 l
Storage quantity of grease:	280 l

Pumping device:

Pump:	SPF 300 KE 2.0
Number of pumps:	1
Max. pumping capacity:	60 m ³ /h
Max. pumping height:	17 m
Operating voltage:	400 V
Mains frequency:	50 Hz
Operating mode:	S2 - 30 min.
Power P1:	3.6 kW
Power P2:	3 kW
Speed:	2,850 U/min
Type of fuse required (electrical protection):	Fuse protection through control unit 400 V
Max. temperature (permanent) of conveyed material:	40 °C
Connection type:	Direct connection
Weight:	44 kg
Impeller type:	Radial impeller with macerating system
Length of mains cable for pump:	5 m
Rated current:	6.2 A
Protection class (pump):	IP 55
Protection class:	I
Type of pump connection cable:	H07RN-F 7G 1.5 mm ²
Temperature monitoring:	integrated
Cos phi - power factor:	0.87
Insulation class:	F

Control:

Control unit:	yes
Operating voltage:	400 V
Mains frequency:	50 Hz
Self-diagnosis system (SDS):	yes
Battery buffering:	no
Multi-line display:	yes
Log book function:	yes
USB interface:	no

GSM interface:	no
Potential-free contact:	yes
Type of fuse required (electrical protection):	3 x C 20 A
Type of fuse required (RCD):	30 mA
Motor protection switch:	yes
Protection class control unit:	IP 54