

# Grease separator EasyClean free NS 7, Standard, Refill inlet



## **Article information**

Item no.: 93007.11 GTIN: 4026092063200 Discount group: 03

### **Advantages**

- Direction of flow can be changed thanks to selfsealing interchangeable hubs
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

# **Description**

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work.

Manual disposal is carried out with the tank open.

20 year polyethylene warranty.

### Version:

Type of disposal:	manual with suction hose
Disposal variant:	Standard
Refill inlet in accordance with DIN 1988:	yes
Nominal size (NS):	7
Inspection window:	no
Shredder-Mix-System:	no
SonicControl:	no
Load-bearing capacity (DIN 19901):	F3

Installation-ready (connection parts must be Delivery state:

connected on site)

General chara	ıcter	เรน	CS

Material: PΕ



#### **Dimensions:**

Set-up area, length:

Set-up area, width:

948 mm

Set-up area, height:

1,653 mm

Required access area, length:

1,910 mm

Required access area, width:

948 mm

Required access area, height:

1,653 mm

#### Tank:

Inlet nominal size (DN):

Inlet nominal size (OD):

Outlet nominal size (DN):

Outlet nominal size (OD):

Outlet nominal size (OD):

Distance pipe bottom inlet to tank bottom:

Distance pipe bottom outlet to tank bottom:

1,255 mm

1,185 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

### Coverage features:

Type of cover:

Cover material:

Colour of cover:

Tightness:

Cover

Polymer

violet

odour-tight

Locking: Quick-release closure

#### Wastewater contents:

Separator contents: 650 l
Total volume: 1,350 l
Contents of sludge trap: 700 l
Storage quantity of grease: 280 l

#### Control:

Control unit: no