

## Grease separator EasyClean free NS 10, Standard, Refill in., Insp. Wind.



### Article information

Item no.: 93010.31  
GTIN: 4026092063415  
Discount group: 03

### Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work.

Manual disposal is carried out with the tank open.

20 year polyethylene warranty.

### Version:

Type of disposal:	manual with suction hose
Disposal variant:	Standard
Refill inlet in accordance with DIN 1988:	yes
Nominal size (NS):	10
Inspection window:	yes
Shredder-Mix-System:	no
SonicControl:	no
Load-bearing capacity (DIN 19901):	F3
Delivery state:	Installation-ready (connection parts must be connected on site)

### General characteristics:

Material: PE

#### Dimensions:

Set-up area, length: 2,822 mm  
Set-up area, width: 951 mm  
Set-up area, height: 1,653 mm  
Required access area, length: 2,590 mm  
Required access area, width: 951 mm  
Required access area, height: 1,653 mm

#### Tank:

Inlet nominal size (DN): 150  
Inlet nominal size (OD): 160 mm  
Outlet nominal size (DN): 150  
Outlet nominal size (OD): 160 mm  
Distance pipe bottom inlet to tank bottom: 1,255 mm  
Distance pipe bottom outlet to tank bottom: 1,185 mm  
Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

#### Coverage features:

Type of cover: Cover  
Cover material: Polymer  
Colour of cover: violet  
Tightness: odour-tight  
Locking: Quick-release closure

#### Wastewater contents:

Separator contents: 900 l  
Total volume: 1,900 l  
Contents of sludge trap: 1,000 l  
Storage quantity of grease: 400 l

#### Control:

Control unit: no