

Grease separator EasyClean free NS 10, Standard, Ref. in., Insp. Wi., SC



Article information

Item no.: 93010.32 GTIN: 4026092063460 Discount group: 03

Advantages

- Direction of flow can be changed thanks to selfsealing interchangeable hubs
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work.

Manual disposal is carried out with the tank open.

20 year polyethylene warranty.

Version:

Type of disposal: manual with suction hose Disposal variant: Standard Refill inlet in accordance with DIN 1988: yes Nominal size (NS): 10 Inspection window: yes Shredder-Mix-System: no SonicControl: ves Load-bearing capacity (DIN 19901): F3

Delivery state: Installation-ready (connection parts must be

connected on site)

General characteristics:



Material:	PE
Dimensions:	
Set-up area, length: Set-up area, width: Set-up area, height: Required access area, length: Required access area, width: Required access area, height:	2,822 mm 951 mm 1,653 mm 2,590 mm 951 mm 1,653 mm
Tank:	
Inlet nominal size (DN): Inlet nominal size (OD): Outlet nominal size (DN): Outlet nominal size (OD): Distance pipe bottom inlet to tank bottom: Distance pipe bottom outlet to tank bottom: Connection inlet/outlet sockets:	150 160 mm 150 160 mm 1,255 mm 1,185 mm PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS
Coverage features:	
Type of cover: Cover material: Colour of cover: Tightness: Locking:	Cover Polymer violet odour-tight Quick-release closure
Wastewater contents:	
Separator contents: Total volume: Contents of sludge trap: Storage quantity of grease:	900 l 1,900 l 1,000 l 400 l
Control:	
Control unit:	no