

## Grease separat. EasyClean Modular free, NS 0.25, Standard, 2-part



### Article information

Item no.: 93025  
GTIN: 4026092030882  
Discount group: 03

### Advantages

- Ideal where access is tight
- can be divided into several parts for insertion, for an insertion opening of max. 66 cm
- Low-maintenance operation

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. Thanks to the modular design, the separator can be inserted even where access is extremely tight. The collecting tank (NS 0.5 with two tanks) made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. A service access cover with odour-tight cover and quick-release closures makes easy access possible for cleaning and maintenance work.

Manual disposal is carried out with the tank open.

20 year polyethylene warranty.

Installation situation: free-standing set-up

### Version:

Type of disposal:	manual with suction hose
Disposal variant:	Standard
Refill inlet in accordance with DIN 1988:	no
Nominal size (NS):	0.25
Inspection window:	no
Shredder-Mix-System:	no
SonicControl:	no
Delivery state:	Installation-ready (connection parts must be connected on site)

### General characteristics:

Material: PE

**Dimensions:**

Set-up area, length:	568 mm
Set-up area, width:	510 mm
Set-up area, height:	710 mm
Height tank bottom up to centre section:	310 mm
Height centre section to top edge of tank:	400 mm

**Tank:**

Inlet nominal size (DN):	50
Inlet nominal size (OD):	50 mm
Outlet nominal size (DN):	50
Outlet nominal size (OD):	50 mm
Distance pipe bottom inlet to tank bottom:	570 mm
Distance pipe bottom outlet to tank bottom:	520 mm
Chamber system:	two-piece chamber
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

**Coverage features:**

Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	black
Tightness:	odour-tight
Locking:	Quick-release closure

**Wastewater contents:**

Separator contents:	28 l
Total volume:	53 l
Contents of sludge trap:	25 l
Storage quantity of grease:	15 l

**Control:**

Control unit:	no
---------------	----