

## Grease separator EasyClean free Basic, NS 4, Direct, right, Refill inlet



### Article information

Item no.: 94004.12DR  
GTIN: 4026092084441  
Discount group: 03

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap.

Two odour-tight covers with quick-release closures allow for easy access for cleaning and maintenance work.

There is a direct disposal pipe socket available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank.

20 year polyethylene warranty.

Installation situation: free-standing set-up

### Version:

Type of disposal:	manual
Disposal variant:	Direct
Refill inlet in accordance with DIN 1988:	yes
Nominal size (NS):	4
Inspection window:	no
Load-bearing capacity (DIN 19901):	F3

Delivery state: Installation-ready (connection parts must be connected on site)

Scope of delivery: Storz-B coupling R 2 1/2" for disposal vehicle connection

### General characteristics:

Material: PE  
Standard: EN 1825

### Dimensions:

Set-up area, length: 1,960 mm  
Set-up area, width: 905 mm  
Set-up area, height: 1,800 mm  
Required access area, length: 1,960 mm  
Required access area, width: 700 mm  
Required access area, height: 1,420 mm

### Tank:

Inlet nominal size (DN): 100  
Inlet nominal size (OD): 110 mm  
Outlet nominal size (DN): 100  
Outlet nominal size (OD): 110 mm  
Distance pipe bottom inlet to tank bottom: 1,055 mm  
Distance pipe bottom outlet to tank bottom: 985 mm  
Pressure pipe connection (DN): 65 mm  
Pressure pipe connection (OD): 75 mm  
Nominal pressure (PN): 10  
Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

### Coverage features:

Type of cover: Cover  
Cover material: Polymer  
Colour of cover: violet  
Tightness: odour-tight  
Locking: Quick-release closure

### Wastewater contents:

Total volume: 820 l  
Contents of sludge trap: 400 l  
Storage quantity of grease: 160 l  
  
Max. grease layer thickness: 180 mm