

## Grease separator EasyClean free Basic, NS 4, Standard, left, Inspection window, Refill inlet



### Article information

Item no.: 94004.32L  
GTIN: 4026092084410  
Discount group: 03

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap.

Two odour-tight covers with quick-release closures allow for easy access for cleaning and maintenance work.

Manual disposal is carried out with the tank open.

20 year polyethylene warranty.

Installation situation: free-standing set-up

### Version:

|   |   |
|---|---|
| Type of disposal:                         | manual with suction hose  |
| Disposal variant:                         | Standard  |
| Refill inlet in accordance with DIN 1988: | yes   |
| Nominal size (NS):                        | 4   |
| Inspection window:                        | yes   |
| Load-bearing capacity (DIN 19901):        | F3  |
| Delivery state:                           | Installation-ready (connection parts must be connected on site) |

### General characteristics:

Material: PE

**Dimensions:**

|                               |          |
|-------------------------------|----------|
| Set-up area, length:          | 1,960 mm |
| Set-up area, width:           | 850 mm   |
| Set-up area, height:          | 1,800 mm |
| Required access area, length: | 1,960 mm |
| Required access area, width:  | 745 mm   |
| Required access area, height: | 1,420 mm |

**Tank:**

|   |   |
|---|---|
| Inlet nominal size (DN):                    | 100   |
| Inlet nominal size (OD):                    | 110 mm  |
| Outlet nominal size (DN):                   | 100   |
| Outlet nominal size (OD):                   | 110 mm  |
| Distance pipe bottom inlet to tank bottom:  | 1,055 mm  |
| Distance pipe bottom outlet to tank bottom: | 985 mm  |
| Pressure pipe connection (DN):              | 65 mm   |
| Pressure pipe connection (OD):              | 75 mm   |
| Nominal pressure (PN):                      | 10  |
| Connection inlet/outlet sockets:            | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |

**Coverage features:**

|                  |                       |
|------------------|-----------------------|
| Type of cover:   | Cover                 |
| Cover material:  | Polymer               |
| Colour of cover: | violet                |
| Tightness:       | odour-tight           |
| Locking:         | Quick-release closure |

**Wastewater contents:**

|                              |        |
|------------------------------|--------|
| Total volume:                | 820 l  |
| Contents of sludge trap:     | 400 l  |
| Storage quantity of grease:  | 160 l  |
| Max. grease layer thickness: | 180 mm |