

Grease separator EasyClean free Basic, NS 10, Standard, universal



Article information

Item no.: 94010.10
GTIN: 4026092084984
Discount group: 03

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap.

Two odour-tight covers with quick-release closures allow for easy access for cleaning and maintenance work.

Manual disposal is carried out with the tank open.

20 year polyethylene warranty.

Installation situation: free-standing set-up

Version:

Type of disposal:	manual with suction hose
Disposal variant:	Standard
Refill inlet in accordance with DIN 1988:	no
Nominal size (NS):	10
Inspection window:	no
Load-bearing capacity (DIN 19901):	F3

Delivery state: Installation-ready (connection parts must be connected on site)

General characteristics:

Material: PE

Dimensions:

Set-up area, length:	2,610 mm
Set-up area, width:	920 mm
Set-up area, height:	1,670 mm
Required access area, length:	2,610 mm
Required access area, width:	920 mm
Required access area, height:	1,670 mm

Tank:

Inlet nominal size (DN):	150
Inlet nominal size (OD):	160 mm
Outlet nominal size (DN):	150
Outlet nominal size (OD):	160 mm
Distance pipe bottom inlet to tank bottom:	1,255 mm
Distance pipe bottom outlet to tank bottom:	1,185 mm
Pressure pipe connection (DN):	65 mm
Pressure pipe connection (OD):	75 mm
Nominal pressure (PN):	10
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

Coverage features:

Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	violet
Tightness:	odour-tight
Locking:	Quick-release closure

Wastewater contents:

Total volume:	1,880 l
Contents of sludge trap:	1,000 l
Storage quantity of grease:	400 l
Max. grease layer thickness:	230 mm