

## Grease separator EasyClean free Basic, NS 7, Direct, right



### Article information

Item no.: 94010.10DR  
GTIN: 4026092084281  
Discount group: 03

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap.

Two odour-tight covers with quick-release closures allow for easy access for cleaning and maintenance work.

There is a direct disposal pipe socket available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank.

20 year polyethylene warranty.

Installation situation: free-standing set-up

### Version:

Type of disposal:	manual
Disposal variant:	Direct
Refill inlet in accordance with DIN 1988:	no
Nominal size (NS):	10
Inspection window:	no
Load-bearing capacity (DIN 19901):	F3

Delivery state: Installation-ready (connection parts must be connected on site)

Scope of delivery: Storz-B coupling R 2 1/2" for disposal vehicle connection

### General characteristics:

Material: PE

Standard: EN 1825

### Dimensions:

Set-up area, length:	2,610 mm
Set-up area, width:	1,000 mm
Set-up area, height:	1,670 mm
Required access area, length:	2,610 mm
Required access area, width:	920 mm
Required access area, height:	1,670 mm

### Tank:

Inlet nominal size (DN):	150
Inlet nominal size (OD):	160 mm
Outlet nominal size (DN):	150
Outlet nominal size (OD):	160 mm
Distance pipe bottom inlet to tank bottom:	1,255 mm
Distance pipe bottom outlet to tank bottom:	1,185 mm
Pressure pipe connection (DN):	65 mm
Pressure pipe connection (OD):	75 mm
Nominal pressure (PN):	10
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

### Coverage features:

Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	violet
Tightness:	odour-tight
Locking:	Quick-release closure

### Wastewater contents:

Total volume:	1,880 l
Contents of sludge trap:	1,000 l
Storage quantity of grease:	400 l
Max. grease layer thickness:	230 mm