

## Grease separat. EasyClean Modular ground, NS 4, Standard, B



### Article information

Item no.: 98204/00B  
 GTIN: 4026092027127  
 Price group: 60

### Advantages

- Vertically adjustable upper section with odour-tight cover plates in various load classes
- Waterproof, resistant to aggressive wastewater
- Low-maintenance operation

### Description

The separator for greasy wastewater is suitable for installation in the ground and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap (NS 4 with separate sludge trap tank) and has a rounded base for fast and clean disposal. Access for cleaning and maintenance work is possible via one or several service access covers.

Manual disposal is carried out with the tank open.

20 year polyethylene warranty.

Installation situation: underground installation

### Version:

Type of disposal:	manual with suction hose
Disposal variant:	Standard
Refill inlet in accordance with DIN 1988:	no
Nominal size (NS):	4
Inspection window:	no
Shredder-Mix-System:	no
SonicControl:	no
Load-bearing capacity (DIN 19901):	E2
Delivery state:	Installation-ready (connection parts must be connected on site)

### General characteristics:

Material: PE  
Standard: DIN 4040-100

### Dimensions:

Max. length: 2,635 mm  
Required access area, length: 1,300 mm  
Required access area, width: 1,300 mm  
Height tank bottom up to centre section: 750 mm  
Height centre section to top edge of tank: 750 mm

### Tank:

Inlet nominal size (DN): 100  
Inlet nominal size (OD): 110 mm  
Outlet nominal size (DN): 100  
Outlet nominal size (OD): 110 mm  
Distance pipe bottom inlet to tank bottom: 1,236 mm  
Distance pipe bottom outlet to tank bottom: 1,136 mm  
Installation depth: 330 - 480 mm  
Groundwater resistant from lower edge of base section: 500 mm  
Clear width of entry (LW): 600 mm  
Chamber system: modular chamber  
Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS

Vertical adjustment: vertically adjustable upper section, can be tilted by 5 degrees

### Coverage features:

Type of cover: Cover plate  
Cover material: Grey iron  
Colour of cover: black  
Load class: B 125 (EN 124)  
Length: 648 mm  
Width: 648 mm  
Height: 95 mm  
Tightness: odour-tight and surface water resistant  
Locking: unlocked

### Wastewater contents:

Separator contents: 1,150 l  
Total volume: 1,750 l  
Contents of sludge trap: 600 l

Storage quantity of grease: 160 l

**Control:**

Control unit: no